
AMERICAN DISH SERVICE

Splash Shield for HT-25 DishMachine

Part #387-6019



CAUTION

Use safety eye-wear whenever drilling metal, use caution with sheet metal parts, corners and edges that can cut or puncture skin if mishandled.

NOTICE

The shield can be used with the model HT-25. This model cannot be converted to a "2-door up" machine and no kit is offered to change the model.

When a shield is desired for the open side of the HT-25 dishmachine, the following instructions are provided to correctly install the splash shield made by ADS.



If the door against the wall on a corner machine is the side chosen to shield, remove the existing tray track rail. This is done by removing the bolts and nuts at the front and rear of the rail.



Remove and keep the locknuts and bolts



... then remove the guide rail from the slot



Forward mounting hole from tray track



Upper mounting hole in front of control box stand



The rear hole is provide in current HT-25. If installing on an older model, drill a hole in the top of the hood on the left hand side, 3.75" from back, 1.875" from side of hood, front hole is 3.75" from front of hood, 1.875" from side of the hood. Hole is for a 1/4" bolt, use a 9/32 (.281") drill for easier fit, seal bolt with flat washer.



Tray track may need to be lowered to fit shield inside



Note: shield tabs should point inward



Fasten the bolt and locknuts on the tray track



Make sure the upper spray arms clear shield



The shield becomes the tray track rail for the racks

Showing finished install of shield

