Model 5AG-ES

American Dish Service Manufacturers of Ware Washing Equipment

High Capacity "Green" Machine

Energy Star® rated: less than 1 gallon per rack

STANDARD FEATURES

- Double duty model double your production
- Large 20.5" door opening washes larger ware
- Stainless steel air gap no leaking back flow preventers
- Dual screens protect pump for cleaner wash arms
- Washes 74 racks per hour with two powerful 1 HP pumps



Optional Pan Rack

Wash sheet pans horizontally



© American Dish Service

For detailed specifications, go to www.americandish.com

900 Blake Street | Edwardsville, Kansas, 66111 Phone: 913.422.3700 | Toll-Free: 800.922.2178 | Fax: 913.422.6630 orders@americandish.com | **americandish.com**

Model 5AG-ES

High Capacity "Green" Machine

Standard Features

- · Cleans 74 racks per hour
- · Water consumption of less than I gallon per rack
- Top mount controls with auto start
- · Two high capacity 1 HP pumps
- Door safety switch & external prime switches
- Delime switch located in the control panel


Get the same great quality & results you expect from ADS while using less water, energy & chemicals








TOP VIEW

Typical Table Details 8.8"— (22.4 cm)









Effective 2/2023

FRONT VIEW

CAUTION:

Electrical and Plumbing connections must be made by a qualified Service Person who will comply with all available federal, state, and local Health, Electrical, Plumbing, and Safety Codes

Manufacturer reserves the right to modify these specifications in compliance with regulatory agencies and manufacturing expediency.



Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Model 5AG-ES Specifications

U.S. REGISTERED PATENTS

Model 5AG-ES			
Rated Capacity (Racks/Hr.) 74	56	46	
Wash Time (Sec.) 50	60	75	
Rinse Time (Sec.) 30	45	60	
Dwell (Sec.)	15	15	
Total Cycle Time (Sec.) 90	120	150	
Water Tank Capacity (Miin) 1.75 Gal (6.74 Liter) Water Temperature (Supply) 120° F Min. (49° C Min) Water Consumption (Per Cycle) 1.78 Gal. (6.74 Liter)			
Motor (2)1.0 HP (0.75 Kw) Electrical Ratings115 Volts, 18 AMP (Single Phase)			

Connect to two Supply Sources using 12 AWG copper wires. Circuit Protection: 20 AMP Circuit Breaker or Fuse with a 20 AMP Rating. OR

Connect to Supply Source using 10 AWG copper wires suitable for at least 167° F (75° C). Circuit Protection: 30 AMP Circuit Breaker or Fuse with a 30 AQMP Rating.

	5" x 19.75" (50.2 cm x 50.2 cm)
Door Clearance	20.5" x 21" (52 cm x 53 cm)
	0.75" FPT
	2.0" Pipe
Height (Door Open)	79.875" (202.9 cm)
Height (Door Closed)	
Width (Overall)	49" (124.5 cm)
Depth (Overall)	34" (86.4 cm)
	446 lb. (202.3 kg)
Shipping Dimensions	60" L x 36" W x 78" H
(152.4 cm x 91.4 cm x 198.1 cm)

American Dish Service Manufacturers of Ware Washing Equipment



© American Dish Service

900 Blake Street | Edwardsville, Kansas, 66111 913.422.3700 | Toll-Free: 800.922.2178 | Fax: 913.422.6630 orders@americandish.com | americandish.com